

GOLD-DRIP[®]

F6

HEAVYWALL DRIPLINE
WITH LONG CYLINDRICAL DRIPPER



PLASTIC-PUGLIA
Irrigation Systems since 1967 

**COMPLETE SYSTEMS
FOR DRIP IRRIGATION**

GOLD-DRIP F6 is a dripline with long cylindrical turbulent flow dripper, self-cleaning with double inlet filter.

F6 is the classic version of the dripline with 6 outlet holes for better water distribution on sandy soils.

TECHNICAL FEATURES	DIAMETER 16 mm	DIAMETER 20 mm
Internal diameter	13,80 mm	17,80 mm
Thickness	45 mil 1,10 mm	45 mil 1,10 mm
Max working pressure	3,50 bar	3,00 bar
Max washing pressure*	4,00 bar	3,50 bar
Nominal flow rate (1,0 bar)	2,00 - 4,00 l/h	2,00 - 4,00 l/h
Dripper spacing	20 ÷ 150 cm	20 ÷ 150 cm
Reel length	400 m	300 m

* For about half an hour with the terminals open

CARACTÉRISTIQUES ET AVANTAGES

- Ideal for long-term surface irrigation systems
- Emission uniformity on long laterals for flat ground
- Resistant to mechanized installation
- High resistance to UV rays, chemicals and acids used in agriculture
- Available with constant or alternating spacing
- Low technological Variation Coefficient (CV)
- Possibility to rewind and reuse for many years
- Dripline compliant with **UNI EN ISO 9261** standards and certified by the **IIP** (Italian Institute of Plastics)



APPLICATIONS

Ideal for long-term irrigation installations such as vineyards, olive groves, fruit trees, screens, flowerbeds and ornamental gardens.

CERTIFIED PRODUCT

 UNI EN ISO 9261:2010

